



**ABRA IMPORT AB**

**ROLLWOOD**  
Holztechnik GmbH  
Spezialfurniere für die Profilmantelung

## **Rollwood – Wrapping Veneer** **Product information**

---



### **ROLLWOOD VENEER** *- the ideal material for wrapping*

**Wrapping veneer on roles, Fingerjointed in length from 1200 mm and up.  
1 or 2 layer of 30 gr. fleece which are glued with D3 glue.  
Unlacquered or lacquered with an waterbased Superflexlacquer.  
Thickness of veneer about 350 my.**

#### **Use**

For wrapping of profiles, panels, doorframes  
Possible at in one process cover both surface  
and edge.

#### **Lacquersurface**

Superflexlacquer, waterbased. Possible to  
get tinted.

We refer to separate productinformation for  
lacquer for further information.

#### **Exempel of suitable base for wrapping**

- MDF
- fibreboard
- solid wood
- aluminium
- composite material

#### **Process**

Normally in special wrapping lines with  
gluesystem of EVA-, PO-, or PU hotmelt.

Depending of machinetype and glue is different  
adjustments necessary in production. Beware of  
suppliers reccomendations.

#### **Veneer Backside**

Supplied with 1 or 2 layer of fleece depending on  
wrapping radius and woodgrain. The fleece could  
also be tinted if necessary.